



INSULATED N UND PE TERMINALS



IK021036



IK021039

SCHRACK INFO

- Snap-on mounting on DIN-rail
- Maximum load 63 A
- Insulated
- Terminal cross-section 16 mm² (e, m) (f with ferrule max. 10 mm²)

DESCRIPTION	PU	TYPE	EAN CODE	AVAILABLE	ORDER NO.
Insulated PE terminal, 15 outlets	1	ISO-SL-KLEM 15	9004840449198		IK021039I
Insulated N terminal, 15 outlets	1	ISO-N-KLEM 15	9004840449181		IK021038I
Insulated PE terminal, 7 outlets	1	ISO-SL-KLEM 7	9004840449075		IK021037I
Insulated N terminal, 7 outlets	1	ISO-N-KLEM 7	9004840449068		IK021036I

N AND PE TERMINALS



IK021036

SCHRACK INFO

- Snap-on mounting on DIN-rail
- Maximum load 63 A
- Terminal cross-section 16 mm² Ye, Ym; Yf with ferrule max. 10 mm²

DESCRIPTION	PU	TYPE	EAN CODE	AVAILABLE	ORDER NO.
NL/PE terminal screw-on type	1	NL/SL-S	9004840086928		BK004405
PE terminal, 15 outlets	1	SL-KLEM 15	9004840022124		IK021039
N terminal, 15 outlets	1	N-KLEM 15	9004840022117		IK021038
PE terminal, 7 outlets	1	SL-KLEM 7	9004840022100		IK021037
N terminal, 7 outlets	1	N-KLEM 7	9004840022094		IK021036



I KNOW WHERE TO FIND IT!

THE SCHRACK TECHNIK WEB SHOP WITH NAVIGATOR
WWW.SCHRACK.COM

- Finding product information made easy
- Buying products around the clock
- Quick access customer service