

Application of Langsol® Cut for PE Lacquers

Manufacturer: LIPPERT-UNIPOL GMBH
Rudolf-Harbig-Weg 10
42781 Haan / Germany

Tel.: +49 (0) 2129 / 9307 - 0
Fax: +49 (0) 2129 / 9307 - 23

Description: **Langsol® Complete 9025**

Product Description

Langsol® Complete 9025 has been developed for high gloss polishing and the removal of haze or small defects on the lacquer.

The composition of the Langsol® Complete 9025 is ideal to remove minor scratches and holograms, leaving a mark-free surface in preparation for finishing

A 1500 grain finish is removed entirely when PE lacquer is used.

The Langsol® Complete 9025 can be used on dark and sensitive surfaces.

A further advantage of the Langsol® Complete 9025: minimal residue on the polished parts and minimal quantity required.

This product meets the highest technical standards. Waste water has not been found to contain any contamination.

Colour	white emulsion
Density at 20 °C	approx. 1,10 g / cm ³
pH - value (Concentrate)	7,0 +- 1,0
Viscosity	10000 - 15000 cP

Dosage / Application

The use of a polishing emulsion facilitates high stock removal and an excellent gloss on all lacquers or lacquered surfaces, in particular light scratches and polish marks are removed. The Langsol® Complete 9025 has been developed for use with standard manual polishing equipment. Please take care to use pads in the correct dimensions.

Storage Conditions

Ideally store at 15 - 25 °C. Temperatures < 4°C should be avoided, since this may cause problems in consistency and stability of the product, which in turn could impair results.