




# Balflex® MULTIPURPOSE Fuel & Gasoline

## Balflex® MULTIPURPOSE OIL, FUEL & GASOLINE – 10.1215.

Oil, Fuel and Gasoline 20bar / 300PSI (100% rubber hose)



**Inner tube:** seamless oil, fuel and gasoline resistant synthetic rubber  
**Reinforcement:** 1 high resistance synthetic fiber braid  
**Outer tube:** black wrapped, weather and abrasion resistant synthetic rubber  
**Safety factor:** 3: 1  
**Application:** oil, fuel and gasoline on automotive, and service stations  
**Temperature range:** - 40°C (- 40°F) + 100°C (+ 212°F)

part number	Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	bar	PSI	bar	PSI	mm	inch	
10.1215.03	3/16"	- 3	4,8	0.19	11,1	0.44	20	300	60	900	50	2.0	0,10
10.1215.04	1/4"	- 4	6,4	0.25	14,0	0.55	20	300	60	900	60	2.4	0,12
10.1215.05	5/16"	- 5	7,9	0.31	15,5	0.61	20	300	60	900	80	3.2	0,15
10.1215.06	3/8"	- 6	9,5	0.37	17,5	0.69	20	300	60	900	100	3.9	0,16
10.1215.08	1/2"	- 8	12,7	0.50	22,0	0.87	20	300	60	900	125	4.9	0,24
10.1215.10	5/8"	- 10	15,9	0.63	26,5	1.04	20	300	60	900	160	6.3	0,27
10.1215.12	3/4"	- 12	19,1	0.75	29,4	1.16	20	300	60	900	190	7.5	0,40
10.1215.16	1"	- 16	25,4	1.00	36,2	1.43	20	300	60	900	254	10.0	0,55

On dash size – 3 (3/16") the outer tube is smooth cover

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.

**Balflex® – The European Technology**