

"TR" polyurethane wheels, cast iron centre



Wheel description

TR polyurethane tread; hardness 95+/-3 Shore A. Cast iron centre.

Ball bearing bore or bore without bearings

The housing is obtained by moulding and turning and contains ball bearings series Z. The hub is available also without bearings.



	150	30	17	30	40	12	700	280	400	1,45	*	652104
	150	35	20	35	47	14	825	290	490	1,60	*	652224
	175	35	20	35	47	14	900	350	650	2,03	*	652105
	200	45	20	45	47	14	1125	380	1000	3,51	*	652106
	200	45	25	45	52	15	1125	380	1000	3,42	*	652206
	250	50	25	50	52	15	1750	400	1200	5,59	*	652108
	300	70	30	70	62	16	3000	550	2200	12,31	*	652109



	150	30	17	30	40	12	700	280	400	0,96	*	654104
	150	35	20	35	47	14	825	290	490	1,36	*	654224
	175	35	20	35	47	14	900	350	650	1,79	*	654105
	200	45	20	45	47	14	1125	380	1000	3,27	*	654106
	200	45	25	45	52	15	1125	380	1000	3,14	*	654206
	250	50	25	50	52	15	1750	400	1200	5,31	*	654108
	300	70	30	70	62	16	3000	550	2200	11,85	*	654109