

Injection polyurethane wheels, polyamide 6 centre, swivel bracket with bolt hole type NL



Wheel description

Injection polyurethane tread; hardness 60 Shore D. Polyamide 6 centre.

Plain bearing bore or roller bearing bore

The plain bearing bore results from a hole in the material forming the centre of the wheel and contains the axle.

In the roller bearing bore, the bearing housing is obtained by moulding and contains cylindrical roller bearings with polyamide 6 cage.

Axle

Axle composed of ground steel bush with bolt according to UNI EN 24017 and nut according to UNI EN 24032.

Swivel bracket with bolt hole type NL

Swivel bracket with bolt hole type NL. The plate and fork are of pressed steel zinc plated finish; swivel actions: double ball greased race. The king pin is integral with top plate and duly rivetted.



	80	30	107	39	73	12	120	0,55	*	607701
	100	30	128	35	73	12	170	0,67	*	607702
	125	35	156	37	80	12	230	0,85	*	607703
	150	35	182	37	73	12	220	1,01	*	607704
	150	45	188	56	102	20	300	1,69	*	607711
	200	50	236	56	102	20	300	2,13	*	607706



	80	30	107	39	73	12	120	0,57	*	607801
	100	30	128	35	73	12	170	0,68	*	607802
	125	35	156	37	80	12	220	0,87	*	607803
	150	35	182	37	73	12	220	1,03	*	607804
	150	45	188	56	102	20	300	1,74	*	607811
	200	50	236	56	102	20	300	2,18	*	607806

