



EUROCEL 901 ALUMINIUM

Short description:

Single sided aluminium foil tape with liner, certified DIN 4102 B1 and classified LNE- M1

Product Data

Backing:	0.030 mm dead soft aluminium foil
Adhesive:	acrylic water based
Liner:	white monosiliconized paper
Total thickness (without liner)	0.058 mm
Adhesion to steel	8.5 N/25mm
Tensile strength MD	50 N/25mm
Elongation at break	6 %
Temp. Resistance	100 °C (short period)

Application

This product is suitable for joining aluminium insulation panels and for conditioning plants

Features	Benefits
Acrylic adhesive	Good adhesion in most applications <ul style="list-style-type: none">➤ Excellent resistance to UV and ageing➤ Good resistance to temperature
Aluminium foil backing	Excellent moisture and vapour barrier <ul style="list-style-type: none">➤ Resistant in most situationsHand tearable➤ Quite adaptable on most surfaces

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss