

3590 cod. 24425

Technical specifications

AR Code	24425
Max Pressure (bar)	140
Max Pressure (psi)	2050
Max flow (lph)	480
Max flow (gph)	127
Max water inlet temperature (°C)	-
Δt	55
Power (Kw)	2.4
RPM	2800
Power (Hz)	1~50
Power (Hz) Power (V)	1~50 230
Power (V)	230
Power (V) Unit size (mm) LxWxH	230 500x730x920
Power (V) Unit size (mm) LxWxH Packaging size	230 500x730x920 51x77x70
Power (V) Unit size (mm) LxWxH Packaging size Weight (Kg)	230 500x730x920 51x77x70 52
Power (V) Unit size (mm) LxWxH Packaging size Weight (Kg) Pallet qty	230 500x730x920 51x77x70 52 6



This website uses cookies to enhance the user experience. If you continue to browse this website, you accept our privacy policy. More details (/en/privacy)

Product details

3 Axial stainless steel pistons wobble-plate pump. Automatic by-pass valve. Boiler start with delay circuit With safety pressure switch to shut-down the boiler in case of lack of water. Motor thermal protector. Vertical boiler, coil cooling function driven by indipendent electric motor, double heating coil w/refractory compound base. 5 m electric cable. Diesel tank 4Lt. Water and diesel filters. 8 m HP type hose, gun and lance with fan jet spray. Brass pump head. Foamer kit with tank (0,5lt)



This website uses cookies to enhance the user experience. If you continue to browse this website, you accept our privacy policy. More details (/en/privacy)

Standard accessories



3520550



3729



40320



41047

50690

Optional accessories



Calibrated and filtered sand 5kg cod. 3207







40898

Rotatory brush cod. 41578

40654

This website uses cookies to enhance the user experience. If you continue to browse this website, you accept our privacy policy. More details (/en/privacy) I understand