



Oscillating motion is far better than conventional orbital motion. Hence suitable for cutting and precision carving.



- ❶ Head of die-cast zinc, ensuring exact and stable housing for the moving parts.
- ❷ Sanding area 65 x 65 x 65mm with gummed pads allows quick changing.
- ❸ Uncompromised safety from class 2 insulation.



The oscillating motion ensures lack of vibration and kickback and allows the fitting of cutting and sawing blades too!

Delta sander OZI 220/E

Small yet unsurpassed in its class!

For grinding surfaces in very tight spots, e.g. corners, sides and inaccessible areas. The oscillating motion ensures quiet operation and also facilitates cutting. The variable speed facility (3,000 - 10,000rpm) ensures the correct speed for every material. Special, balanced, low noise DC motor with high life expectancy. Main housing of glass-fibre reinforced POLYAMIDE. Complete with 4 sanding discs (2x 80 grit, 1x 150 grit and 1x 240 grit).

Technical data:

220 - 240V. 100W. Sanding frequency of 3,000 - 10,000rpm. Length 230mm. Weight 550g. Insulated to class 2.

NO 28 520

Important:

The self-adhesive sanding pads ensure quick changing and optimum usage. Simply remove and rotate through 120° for a fresh corner.



The delta sander OZI 220/E is supplied in a high-grade polypropylene storage case. It is attractive, extremely stable and sufficiently large to enable the machine to be replaced in it after completion of the work without fiddly refitting. A clear label on the side identifies the contents.

Flexible spatula made from spring steel for OZI

Suitable for the removal of paint, adhesive residues (tile adhesive), for digging out old silicone from joints, but also for treating cars (abrasion of tar and underbody protection). 50 x 70mm.

NO 28 904



Sanding pads for OZI

High durability corundum (aluminium oxide) pads. Grain filled with special filler to prevent premature clogging. Deposited on special backing paper. Self-adhesive.



Standard packing

NO 28 880	80 grit	5 pieces
NO 28 882	150 grit	5 pieces
NO 28 886	240 grit	5 pieces

Bulk packing

NO 28 891	80 grit	25 pieces
NO 28 893	150 grit	25 pieces
NO 28 895	240 grit	25 pieces

HSS cutting blade for OZI



Oscillates, making it ideal for cutting metal, wood, PC cards, plastics, plaster of Paris and many other materials. The segment cut facilitates exact cutting right into corners.

NO 28 900 Ø 65mm



Diamond cutting blade for OZI

Operation as described above for the HSS blade. Cuts marble, bricks, dry walling and many other materials. Ideal for interior finishing and sanitary and electrical installation.

NO 28 902 Ø 65mm



Diamond files for OZI

For dulling, de-burring and post-processing of glass, porcelain and ceramics. For grinding and de-burring of hardened and unhardened steel. A radius on one side makes it possible to work at round, recessed spots. Width 25mm. Immersion depth 20mm.

NO 28 906	120 grit
NO 28 907	180 grit



HSS immersion saw blades for OZI

For exact square excavations and other forms. For making hatchways and windows in ship and aircraft models. Cuts wood, plywood, plastics and aluminium. Max. immersion depth 16mm.

NO 28 897	saw blade width	8mm
NO 28 898	saw blade width	14mm



For precision square excavations, HSS immersion saw blades are available with an 8 and 14mm width of cut.

Suitable accessories:

MICROMOT tool holder
Footswitch FS

Ташев-Галвинг ООД
www.tashev-galving.com